

CIM12R/UC24-240V

Multifunction | 24 ... 240 V AC / DC | 1 TRIAC



Time data	
Timing functions	fig. 1 1: E 2: A, K, N, B1, S, LS 3: B, W
Timing range	50 ms ... 60 h
Timing scale	0.6 s / 6 s / 60 s / 6 min / 60 min / 6 h / 60 h

Main circuit	
Number of outputs	1 NO
Output type	⚡ TRIAC
Rated voltage	250 V AC
Switching at zero crossing	yes ($t_d > 0.6$ s)
Rated current	2 A
Minimum load	50 mA, 12 V
Inrush current	100 A, 10 ms
Rated limit load	78 A²s
Typ. leakage current	1 mA
Rated load AC-1	300 VA
Mechanical endurance (cycles)	∞
Electrical endurance at rated load AC-1 (cycles)	∞

Control circuit	
Nominal voltage	24 ... 240 V AC / DC
Operating voltage range	16.8 ... 250 V AC / DC
Power consumption AC / DC	1.2 VA / 430 mW
Current consumption on supply A1-A2 AC / DC	< 23 mA / < 23 mA
Current consumption on input control B1 AC / DC	< 22 mA / < 22 mA
Threshold voltage on input control B1 AC / DC	13 V / 15 V
Frequency range	0; 16 ... 63 Hz

Insulation	
Rated test voltage control / main circuit	2.5 kV rms / 1 min
Pollution degree	2
Overvoltage category	III

General data	
Storage temperature (no ice)	-40 ... 85 °C
Operation temperature	-40 ... 70 °C
Conductor cross section control / main circuit	2.5 mm², 2 x 1.5 mm²
Nominal screw torque control / main circuit	0.5 Nm
Dimensions	fig. 2
Weight	70 g
Ingress Protection	IP 20
Housing material	PA

Product references		
Description	Type	24-240
AC / DC Supply	CIM12R/UC...V	✓
Other voltages on request. Please contact support@comatreleco.com.		
«...» List control circuit voltage to complete product references.		




fig. 1. Wiring diagram





fig. 2. Dimensions (mm)



Technical approvals, conformities

Standards IEC/EN 61812-1

Railway EN 45545-2; EN 50155

Approvals     