

US7-B5-RA28


US7-Bxx-xxx



HMI		
Display	7" (16:9) touchscreen, TFT, LCD, 65 536 (16 bit) colors	
Resolution	800 x 480 pixels (WVGA)	
Power supply		
Nominal voltage	24 V DC	
Inputs		
Number of digital inputs	14	
Number of encoder inputs*	2	
Number of analog inputs*	2	
Number of temperature inputs	2 PT100/NI100/NI120/PT1000/NI1000 Number of temperature inputs	
Outputs		
Number of transistor outputs	10	
Number of analog outputs	2	
Memory		
Number of ladder code memory (virtual)	1,000 KB	
Execution time	0.13 µs	
Memory card	Micro SD-Card	
Internal memory	RAM: 512 MB (-B5) / 1 GB (-B10) ROM: 3 GB system memory (-B5) / 6 GB (-B10) ROM: 1 GB user memory (-B5) / 2 GB (-B10)	
Communication		
Connections	RS232 RS485 CAN	
Modules	Add up to 3 COM modules	
Protocol	MQTT Client, EtherNet/IP, MODBUS TCP, CANopen, CANlayer2, UniCAN, SNMP, BACnet, KNX and M-Bus via gateway, Message Composer for 3rd party protocols	
General data		
Storage temperature (no ice)	-30 ... 70 °C / -22 ... 158 °F	
Operation temperature	-20 ... 55 °C / -4 ... 131 °F	
Back-up battery	Model: 3V CR2032, Battery lifetime: 4 years typical at 25 °C, battery back-up for all memory and RTC	
Dimensions	see fig. 1	
Mounting	Panel with brackets	
Ingress Protection	IP 20 / NEMA1 (case), IP 66 / NEMA4X (front Panel)	
Relative humidity, no condensation	5 ... 95 %	
Product references		
Description	Type	24
14 digital, including 2 HSC, 2 analog, 2 temperature inputs 8 relay, 2 analog outputs	US7-B5-RA28	✓
Other devices on request. Please contact support@comatreleco.com . The UniLogic software is available free of charge on www.unitronicsplc.com at downloads.		
Accessories		
Expansion Adapters	UAG-CX-XKP125, UAG-CX-XKP300, UAG-CX-XKPL600, UAG-CX-XKPL1200, UAG-CX-XKPL1500, UAG-CX-XKPL2000, UAG-CX-XKPL3000	
Uni-COM	UAC-CX-01RS2, UAC-CX-01RS4, UAC-CX-01CAN	
I/O Expansion Modules	IO-DI8-T08, IO-DI8-R04, IO-DI8-R08, IO-DI16, IO-T016, IO-R08, IO-R016, IO-DI8ACH, IO-AI4-A02, IO-PT400, IO-PT4K, IO-A06X, IO-LC1, IO-LC3, IO-ATC8, IO-AI8, IO-D16A3-R016, EX-D16A3-R08, EX-D16A3-T016, EX-A2X, EX-RC1	
Routers	UCR-ST-B5-EU, UCR-ST-B8-EU	
DIN rail kit for UCR B5/B8	UCR-OP-B5-DIN	



fig. 1. Dimensions (mm)



Technical approvals, conformities

Approvals    