

UIS-WCB1  
UID-xxx / UIA-xxx / UIS-xxx

|                              |                                                  |
|------------------------------|--------------------------------------------------|
| <b>Inputs</b>                |                                                  |
| Number of digital inputs     | 10                                               |
| Number of encoder inputs*    | 2                                                |
| Number of analog inputs*     | 2                                                |
| Number of temperature inputs | 2 PT100/Ni100/Ni120 Number of temperature inputs |


|                              |   |
|------------------------------|---|
| <b>Outputs</b>               |   |
| Number of relay outputs      | 8 |
| Number of transistor outputs | 2 |
| Number of analog outputs     | 2 |

|                                    |                                |
|------------------------------------|--------------------------------|
| <b>General data</b>                |                                |
| Storage temperature (no ice)       | -30 ... 70 °C / -22 ... 158 °F |
| Operation temperature              | -20 ... 55 °C / -4 ... 131 °F  |
| Dimensions                         | see fig. 1                     |
| Mounting                           | DIN rail                       |
| Ingress Protection                 | IP 20 / NEMA1                  |
| Relative humidity, no condensation | 5 ... 95 %                     |

| <b>Product references</b>                                                                                                  |          |    |
|----------------------------------------------------------------------------------------------------------------------------|----------|----|
| Description                                                                                                                | Type     | 24 |
| 10 digital, 2 HSC/shaft encoder, 2 analog, 2 PT100/Ni100/Ni120 inputs   2 Transistor, 2 PWM/HSO, 8 relay, 2 analog outputs | UIS-WCB1 | ✓  |
| Other devices on request. Please contact <a href="mailto:support@comatreleco.com">support@comatreleco.com</a> .            |          |    |



fig. 1. Dimensions (mm)



Technical approvals, conformities

Standards IEC 60068-2-27; IEC 60068-2-6

Approvals   