

# C12-A21/AC48V

2 pole | changeover contact | Faston



## Main circuit

|                                                  |                  |
|--------------------------------------------------|------------------|
| Available contact materials                      | AgNi + 0.2 µ Au  |
| Recommended minimum contact load                 | 10 mA / 10 V     |
| Maximum contact load AC                          | 5 A / 250 V AC-1 |
| Maximum contact load DC                          | 5 A / 30 V DC-1  |
| Inrush current                                   | 15 A, 20 ms      |
| Rated load AC                                    | 1 200 VA         |
| Rated load DC                                    | fig. 3.          |
| Rated current                                    | 5 A              |
| Mechanical endurance (cycles)                    | ≥ 10 000 000     |
| Electrical endurance at rated load AC-1 (cycles) | ≥ 100 000        |

## Control circuit

|                           |                                           |
|---------------------------|-------------------------------------------|
| Nominal voltage           | see table product references              |
| Operating voltage range   | 0.8 U <sub>N</sub> ... 1.1 U <sub>N</sub> |
| Pick-up voltage           | ≤ 0.8 U <sub>N</sub>                      |
| Release voltage           | ≥ 0.1 U <sub>N</sub>                      |
| Power consumption AC / DC | 1.1 VA / 0.7 W                            |

## Coil table

| V AC | Ohm   | mA |
|------|-------|----|
| 48   | 1 206 | 23 |

## Insulation

|                                |              |
|--------------------------------|--------------|
| Test voltage open contact      | 1 kV / 1 min |
| Test voltage contact / contact | 3 kV / 1 min |
| Test voltage contact / coil    | 5 kV / 1 min |
| Overvoltage category           | III          |
| Insulation resistance at 500 V | ≥ 1 GΩ       |
| Pollution degree               | 3            |

## General data

|                                           |                |
|-------------------------------------------|----------------|
| Storage temperature (no ice)              | -40 ... 80 °C  |
| Operation temperature                     | -40 ... 60 °C  |
| Pick-up time / bounce time                | 10 ms / ≤ 1 ms |
| Release time / bounce time                | 5 ms / ≤ 3 ms  |
| Maximum switching frequency at rated load | 1 200 / h      |
| Weight                                    | 21 g           |
| Housing material                          | PA / PC        |

## Product references

| Description | Type           | 48 |
|-------------|----------------|----|
| AC 50 Hz    | C12-A2x/AC...V | ✓  |

AC relays also available as 60 Hz. Other voltages on request. Please contact support@comatreleco.com.  
«...» List coil voltage to complete product references.

## Accessories

|        |                    |
|--------|--------------------|
| Socket | S12, S12-PI, S12-P |
|--------|--------------------|




fig. 1. Wiring diagram




fig. 2. AC voltage endurance



fig. 3. DC load limit curve





fig. 4. Dimensions (mm)



## Technical approvals, conformities

Standards IEC/EN 60947; IEC/EN 61810

