

V200-18-E1B  
V200-18-xxx




|                                    |                               |
|------------------------------------|-------------------------------|
| <b>Power supply</b>                |                               |
| Nominal voltage                    | 24 V DC                       |
| <b>Inputs</b>                      |                               |
| Number of digital inputs           | 16                            |
| Number of encoder inputs*          | 2                             |
| Number of analog inputs*           | 3                             |
| <b>Outputs</b>                     |                               |
| Number of relay outputs            | 10                            |
| Number of transistor outputs       | 4                             |
| <b>General data</b>                |                               |
| Storage temperature (no ice)       | -20 ... 60 °C / -4 ... 140 °F |
| Operation temperature              | 0 ... 50 °C / 32 ... 122 °F   |
| Dimensions                         | see fig. 1                    |
| Ingress Protection                 | IP 20 / NEMA1                 |
| Relative humidity, no condensation | 5 ... 95 %                    |

| <b>Product references</b>                                                                                       |             |    |
|-----------------------------------------------------------------------------------------------------------------|-------------|----|
| Description                                                                                                     | Type        | 24 |
| 16 digital, 2 HSC/shaft encoder, 3 analog inputs   4 transistor, 2 PWM/HSO, 10 relay outputs                    | V200-18-E1B | ✓  |
| Other devices on request. Please contact <a href="mailto:support@comatreleco.com">support@comatreleco.com</a> . |             |    |



fig. 1. Dimensions (mm)



Technical approvals, conformities

Approvals    