

URA-0800U
URA-xxx / URB-xxx / URD-xxx / URS-xxx / URP-xxx



Power supply							
Nominal voltage	24 V DC						
Inputs							
Number of analog inputs*	8						
Communication							
Connections	Ethernet						
Modules	Up to 63 I/O per adapter						
Resolution	16-bit Analog						
General data							
Storage temperature (no ice)	-40 ... 70 °C / -40 ... 158 °F						
Operation temperature	-40 ... 70 °C / -40 ... 158 °F						
Dimensions	Slim modules – 12 mm only						
Mounting	DIN rail						
Ingress Protection	IP 20 / NEMA1						
Relative humidity, no condensation	5 ... 90 %						
Product references							
<table><tr><th>Description</th><th>Type</th></tr><tr><td>8 analog voltage inputs 16-bit, 10 pin</td><td>URA-0800U</td></tr><tr><td colspan="2">Other devices on request. Please contact support@comatreleco.com.</td></tr></table>		Description	Type	8 analog voltage inputs 16-bit, 10 pin	URA-0800U	Other devices on request. Please contact support@comatreleco.com .	
Description	Type						
8 analog voltage inputs 16-bit, 10 pin	URA-0800U						
Other devices on request. Please contact support@comatreleco.com .							
Accessories							
Remote I/O	URP-PS24V, URP-END						



Technical approvals, conformities

Standards IEC 60068-2-27; IEC 60068-2-6

Approvals   