

URA-0800T  
URA-xxx / URB-xxx / URD-xxx / URS-xxx / URP-xxx



| <b>Power supply</b>                                                                                                                                                                                                                                                             |                                |             |      |                                        |           |                                                                                                                 |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|-------------|------|----------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------|--|
| Nominal voltage                                                                                                                                                                                                                                                                 | 24 V DC                        |             |      |                                        |           |                                                                                                                 |  |
| <b>Inputs</b>                                                                                                                                                                                                                                                                   |                                |             |      |                                        |           |                                                                                                                 |  |
| Number of analog inputs*                                                                                                                                                                                                                                                        | 8                              |             |      |                                        |           |                                                                                                                 |  |
| <b>Communication</b>                                                                                                                                                                                                                                                            |                                |             |      |                                        |           |                                                                                                                 |  |
| Connections                                                                                                                                                                                                                                                                     | Ethernet                       |             |      |                                        |           |                                                                                                                 |  |
| Modules                                                                                                                                                                                                                                                                         | Up to 63 I/O per adapter       |             |      |                                        |           |                                                                                                                 |  |
| Resolution                                                                                                                                                                                                                                                                      | 16-bit Analog                  |             |      |                                        |           |                                                                                                                 |  |
| <b>General data</b>                                                                                                                                                                                                                                                             |                                |             |      |                                        |           |                                                                                                                 |  |
| Storage temperature (no ice)                                                                                                                                                                                                                                                    | -40 ... 70 °C / -40 ... 158 °F |             |      |                                        |           |                                                                                                                 |  |
| Operation temperature                                                                                                                                                                                                                                                           | -40 ... 70 °C / -40 ... 158 °F |             |      |                                        |           |                                                                                                                 |  |
| Dimensions                                                                                                                                                                                                                                                                      | Slim modules – 12 mm only      |             |      |                                        |           |                                                                                                                 |  |
| Mounting                                                                                                                                                                                                                                                                        | DIN rail                       |             |      |                                        |           |                                                                                                                 |  |
| Ingress Protection                                                                                                                                                                                                                                                              | IP 20 / NEMA1                  |             |      |                                        |           |                                                                                                                 |  |
| Relative humidity, no condensation                                                                                                                                                                                                                                              | 5 ... 90 %                     |             |      |                                        |           |                                                                                                                 |  |
| <b>Product references</b>                                                                                                                                                                                                                                                       |                                |             |      |                                        |           |                                                                                                                 |  |
| <table><tr><th>Description</th><th>Type</th></tr><tr><td>8 analog current inputs 16-bit, 10 pin</td><td>URA-0800T</td></tr><tr><td colspan="2">Other devices on request. Please contact <a href="mailto:support@comatreleco.com">support@comatreleco.com</a>.</td></tr></table> |                                | Description | Type | 8 analog current inputs 16-bit, 10 pin | URA-0800T | Other devices on request. Please contact <a href="mailto:support@comatreleco.com">support@comatreleco.com</a> . |  |
| Description                                                                                                                                                                                                                                                                     | Type                           |             |      |                                        |           |                                                                                                                 |  |
| 8 analog current inputs 16-bit, 10 pin                                                                                                                                                                                                                                          | URA-0800T                      |             |      |                                        |           |                                                                                                                 |  |
| Other devices on request. Please contact <a href="mailto:support@comatreleco.com">support@comatreleco.com</a> .                                                                                                                                                                 |                                |             |      |                                        |           |                                                                                                                 |  |
| <b>Accessories</b>                                                                                                                                                                                                                                                              |                                |             |      |                                        |           |                                                                                                                 |  |
| Remote I/O                                                                                                                                                                                                                                                                      | URP-PS24V, URP-END             |             |      |                                        |           |                                                                                                                 |  |



Technical approvals, conformities

Standards IEC 60068-2-27; IEC 60068-2-6

Approvals   