

CMA-U111/UC24V

0 ... 10 V | 0 ... 10 V | AUTO-OFF-MAN | feedback contact

Power supply	
Nominal voltage	24 V AC/DC
Operating voltage range	-15 ... 10 %
Power consumption AC / DC	1 VA / 0.6 W
Frequency range	45 ... 65 Hz
Inputs	
Number of analogue inputs	1
Número de entradas analógicas	0 ... 10 V
Outputs	
Number of analogue ouputs	1
Nominal range analogue outputs	0 ... 10 V
Insulation	
Type of insulation	basic
Overvoltage category	III
Pollution degree	2
General data	
Storage temperature (no ice)	-40 ... 85 °C
Operation temperature	-25 ... 65 °C
Conductor cross section control / main circuit	2.5 mm², 2 x 1.5 mm²
Nominal screw torque control / main circuit	0.5 Nm
Ingress Protection	IP 20
Mounting	TH35 (IEC 60715)
Mounting distance	0
Operation Position	Any
Categories of environmental protection	RT III
Dimensions	fig. 2
Weight	53 g
Housing material	PA66

Product references		
Description	Type	24
analog 0 ... 10 V	CMA-U111/UC...V	✓

“...” List control circuit voltage to complete product references. For customized kits please contact support.

Accessories	
2-pole potential bridge bar	V10-G (BAG 5 PCS)
4-pole potential bridge bar	V44-G (BAG 5 PCS)
8-pole potential bridge bar	V84-G (BAG 5 PCS)




fig. 1. Wiring diagram





fig. 2. Dimensions (mm)



Technical approvals, conformities

Approvals