

UAG-XKPL1500  
UAG-XKxxx / UAG-CXxxx



|                         |                                |
|-------------------------|--------------------------------|
| <b>Power supply</b>     |                                |
| Nominal voltage         | 12 or 24 V DC                  |
| Operating voltage range | 10.2 ... 28.8 V DC             |
| Power consumption DC    | 0.9 A @12 V DC, 0.5 A @24 V DC |

|                                    |                                  |
|------------------------------------|----------------------------------|
| <b>General data</b>                |                                  |
| Storage temperature (no ice)       | -30 ... 70 °C / -22 ... 140 °F   |
| Operation temperature              | -20 °C ... 55 °C / -4 ... 131 °F |
| Mounting                           | DIN rail                         |
| Ingress Protection                 | IP 20 / NEMA1                    |
| Relative humidity, no condensation | 5 ... 95%                        |

| <b>Product references</b>                                                                                       |              |       |
|-----------------------------------------------------------------------------------------------------------------|--------------|-------|
| Description                                                                                                     | Type         | 12-24 |
| Long range adapter kit                                                                                          | UAG-XKPL1500 | ✓     |
| Other devices on request. Please contact <a href="mailto:support@comatreleco.com">support@comatreleco.com</a> . |              |       |

**UAG-XK**  
Both the Base and End units of these adapters have DIN rail clips.

**UAG-CX**  
The base unit of these adapters has a plug; the end unit has DIN rail clips.



Technical approvals, conformities

Standards IEC 60068-2-27; IEC 60068-2-6

Approvals   