

URD-0016CG-8  
URA-xxx / URB-xxx / URD-xxx / URS-xxx / URP-xxx



|                                    |                                |
|------------------------------------|--------------------------------|
| <b>Power supply</b>                |                                |
| Nominal voltage                    | 24 V DC                        |
| <hr/>                              |                                |
| <b>Outputs</b>                     |                                |
| Number of transistor outputs       | 16                             |
| Rated current                      | 0.3 A                          |
| <hr/>                              |                                |
| <b>Communication</b>               |                                |
| Connections                        | Ethernet                       |
| Modules                            | Up to 63 I/O per adapter       |
| Resolution                         | 16-bit Analog                  |
| <hr/>                              |                                |
| <b>General data</b>                |                                |
| Storage temperature (no ice)       | -40 ... 70 °C / -40 ... 158 °F |
| Operation temperature              | -40 ... 70 °C / -40 ... 158 °F |
| Dimensions                         | Slim modules – 12 mm only      |
| Mounting                           | DIN rail                       |
| Ingress Protection                 | IP 20 / NEMA1                  |
| Relative humidity, no condensation | 5 ... 90 %                     |

|                                                                                                                 |              |           |
|-----------------------------------------------------------------------------------------------------------------|--------------|-----------|
| <b>Product references</b>                                                                                       |              |           |
| <b>Description</b>                                                                                              | <b>Type</b>  | <b>24</b> |
| 16 digital outputs (sink), 18 pin                                                                               | URD-0016CG-8 | ✓         |
| Other devices on request. Please contact <a href="mailto:support@comatreleco.com">support@comatreleco.com</a> . |              |           |

|                    |                    |  |
|--------------------|--------------------|--|
| <b>Accessories</b> |                    |  |
| Remote I/O         | URP-PS24V, URP-END |  |



Technical approvals, conformities

Standards IEC 60068-2-27; IEC 60068-2-6

Approvals   