### **CMS-ANT-KAB**

# GSM Antenna cable | SMA male / female | 2.5 m | 5 m | 10 m | 20 m



Communication

Frequencies  $0 \sim 6 \text{ Ghz}$ Antenna connector type SMA male / female

Cable type / length RG-58 / 2.5 m | 5 m | 10 m | 20 m

 $\begin{array}{ll} \text{Impedance} & 50~\Omega \\ \text{Max bending radius} & 25~\text{mm} \end{array}$ 

#### **Housing and environmental conditions**

Storage temperature (no ice)

-20 ... 80 °C

Operation temperature

-20 ... 80 °C

Ingress Protection

IP67 only when mated

Mounting

Panel mount option, see fig. 1

Housing material PE
Dimensions see fig. 2

Weight 90 g (2.5 m) | 180 g (5 m) | 340 g (10 m) | 630 g (20 m)

#### **Product references**

Description	Туре	2.5	5	10	20
Antenna cable	CMS-ANT-KAB/M	✓	$\checkmark$	$\checkmark$	$\checkmark$


"..." List cable length to complete product references.

Other cable length on request. Please contact support@comatreleco.com.





## fig. 1. Mounting



RECOMMENDED TORQUE FOR PANEL NUT: 150Ncm

## fig. 2. Dimensions (mm)

17/4°-36UNS 25.0±3 25.0±3

## Technical approvals, conformities

Standards RoHs: compliant